



**Part Number:** 1583ENH

Cat 5e Cable, U/UTP, LSZH, 4 Pair, AWG 24, Indoor CPR Dca

### Product Description

CAT5e (100MHz), 4-Pair, U/UTP Unshielded, Premise Horizontal Cable, 24 AWG solid bare copper conductors, Polyethylene insulation, LSZH jacket, RJ-45 compatible

### Technical Specifications

#### Product Overview

Suitable Applications:	Horizontal and building backbone cable; Support current and future Category 5e applications, such as: 1000Base-T (Gigabit Ethernet), 100 Base-T, 10 Base-T, FDDI, ATM
------------------------	---

#### Physical Characteristics (Overall)

##### Conductor

Element	AWG	Stranding	Material	No. of Pairs
Individual pair	24	Solid	BC - Bare Copper	4

Conductor Count:	8
Total Number of Pairs:	4

##### Insulation

Element	Type	Material	Nominal Diameter
Individual pair	Dielectric	Polyethylene	0.9 mm

Bonded-Pair:	No
--------------	----

##### Color Chart

Number	Color
Pair 1	White/Blue & Blue
Pair 2	White/Green & Green
Pair 3	White/Orange & Orange
Pair 4	White/Brown & Brown

##### Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance
LSZH / FRNC	4.9 mm	0.3 mm

#### Construction and Dimensions

Min Elongation at Breakof Conductors:	10 %
Min Elongation at Breakof Insulation:	100 %
Min Elongation at Breakof Jacket:	100 %
Min Tensile Strength of Jacket:	9 MPa

#### Electrical Characteristics

##### Conductor DCR

Max. Conductor DCR	Max DCR Unbalanced Between Pairs [%]	Max. DCR Unbalanced Within Pair [%]
95 Ohm/km	4 %	2 %

##### Capacitance

<b>Max. Capacitance Unbalance</b>	<b>Max. Mutual Capacitance</b>
1,600 pF/m	56 pF/m

#### Impedance

<b>Nominal Characteristic Impedance</b>
100 Ohm

#### Delay

<b>Max. Delay Skew</b>	<b>Min. Velocity of Propagation</b>
40 ns/100m	60 %

#### High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACR [dB]	Min. PSACR [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]	Min. TCL [dB]	Min. ELTCTL [dB]
1 MHz	2.1 dB/100m	65.3 dB	62.3 dB	63.2 dB	60.2 dB	64 dB	61 dB	20 dB	40 dB	35 dB
4 MHz	4 dB/100m	56.3 dB	53.3 dB	52.32 dB	49.3 dB	52 dB	49 dB	23 dB	34 dB	23 dB
10 MHz	6.3 dB/100m	50.3 dB	47.3 dB	44 dB	41 dB	44 dB	41 dB	25 dB	30 dB	15 dB
16 MHz	8 dB/100m	47.2 dB	44.2 dB	39.2 dB	36.2 dB	39.9 dB	36.9 dB	25 dB	28 dB	10.9 dB
20 MHz	9 dB/100m	45.8 dB	42.8 dB	36.8 dB	33.8 dB	38 dB	35 dB	25 dB	27 dB	9 dB
31.25 MHz	11.4 dB/100m	42.9 dB	39.9 dB	31.5 dB	28.5 dB	34.1 dB	31.5 dB	23.6 dB	25.1 dB	5.5 dB
62.5 MHz	16.5 dB/100m	38.4 dB	35.4 dB	21.9 dB	18.9 dB	28.1 dB	25.1 dB	21.5 dB	22 dB	
100 MHz	21.3 dB/100m	35.3 dB	32.3 dB	14 dB	11 dB	24 dB	21 dB	20.1 dB	20 dB	

High Freq Table Note: Limits below 4 MHz are for information only. Reference standard: ISO/IEC 61156-5 ed. 2.0 (2009)

General Electrical Parameters Notes: Reference standard: ISO/IEC 61156-5 ed. 2.0 (2009)

Segregation class according EN50174-2: a

#### Current

<b>Max. Recommended Current [A]</b>
1.5 A

#### Voltage

<b>Voltage Rating [V]</b>
72 V

#### Temperature Range

Installation Temp Range:	0°C To +50°C
Operating Temp Range:	-30°C To +60°C

#### Mechanical Characteristics

Bulk Cable Weight:	28 kg/km
Max Recommended Pulling Tension:	65 N
Min Bend Radius During Installation:	40 mm
Min Bend Radius During Operation:	20 mm

#### Standards

ISO/IEC Compliance:	ISO/IEC 11801 Ed. 2.2:2002/A2:2010/C1:2011
CPR Euroclass:	Dca-s2,d2,a1
CENELEC Compliance:	EN 50173-1 Ed. 3:2011
Data Category:	Category 5e
ANSI Compliance:	ANSI/TIA 568.2-D (2018)
IEEE Specification:	PoE: IEEE 802.3bt Type 1, Type 2, Type 3

#### Applicable Environmental and Other Programs

Environmental Space:	Indoor - Euroclass Dca
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01

#### Flammability, LS0H, Toxicity Testing

ISO/IEC Flammability:	IEC 60332-1-2
Burning Load:	285 kJ/m
Amount of Halogen acc. to IEC 60754-1 & EN50267-1:	Zero

## Part Number

### Variants

Item #	Color	Length
1583ENH.10U305	Black	305 m
1583ENH.01305	Blue	305 m
1583ENH.01500	Blue	500 m
1583ENH.01U305	Blue	305 m
1583ENH.K1305	Blue	305 m
1583ENH.011000	Blue	1,000 m
1583ENH.001000	Gray	1,000 m
1583ENH.00305	Gray	305 m
1583ENH.003570	Gray	3,570 m
1583ENH.00500	Gray	500 m
1583ENH.00B100	Gray	100 m
1583ENH.00U305	Gray	305 m
1583ENH.K0305	Gray	305 m
1583ENH.02U305	Green	305 m
1583ENH.04500	Orange	500 m
1583ENH.04U305	Orange	305 m
1583ENH.07500	Red	500 m
1583ENH.07U305	Red	305 m
1583ENH.05U305	Violet	305 m
1583ENH.05500	Violet	500 m
1583ENH.09U305	White	305 m
1583ENH.03U305	Yellow	305 m
1583ENH.031000	Yellow	1,000 m

Patent: <https://www.belden.com/resources/patents>

### History

Update and Revision: Revision Number: 0.210 Revision Date: 09-17-2019

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.